DIM600DCM17-A000

IGBT Chopper Module

Replaces September 2001, version DS5491-1.1

DS5491-2.0 March 2002

FEATURES

- 10µs Short Circuit Withstand
- High Thermal Cycling Capability
- Non Punch Through Silicon
- Isolated MMC Base with AlN Substrates

APPLICATIONS

- Choppers
- Motor Controllers
- Traction Drives

The Powerline range of modules includes half bridge, chopper, dual and single switch configurations covering voltages from 600V to 3300V and currents up to 2400A.

The DIM600DCM17-A000 is a 1700V, n channel enhancement mode insulated gate bipolar transistor (IGBT) chopper module. The IGBT has a wide reverse bias safe operating area (RBSOA) plus full 10µs short circuit withstand. This module is optimised for traction drives and other applications requiring high thermal cycling capability.

The module incorporates an electrically isolated base plate and low inductance construction enabling circuit designers to optimise circuit layouts and utilise grounded heat sinks for safety.

ORDERING INFORMATION

Order As:

DIM600DCM17-A000

Note: When ordering, please use the whole part number.

KEY PARAMETERS

V_{CES}		**1700V**
$V_{CE(sat)}$*	**(typ)**	**2.7V**
I_C	**(max)**	**600A**
$I_{C(PK)}$	**(max)**	**1200A**

*(measured at the power busbars and not the auxiliary terminals)



Fig. 1 Chopper circuit diagram



Outline type code: D

(See package details for further information)

Fig. 2 Electrical connections - (not to scale)

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

ABSOLUTE MAXIMUM RATINGS - PER ARM

Stresses above those listed under 'Absolute Maximum Ratings' may cause permanent damage to the device. In extreme conditions, as with all semiconductors, this may include potentially hazardous rupture of the package. Appropriate safety precautions should always be followed. Exposure to Absolute Maximum Ratings may affect device reliability.

T_{case} = 25˚C unless stated otherwise

Symbol	Parameter	Test Conditions	Max.	Units
V_{CES}	Collector-emitter voltage	V_{GE} = 0V	1700	V
V_{GES}	Gate-emitter voltage	-	±20	V
I_C	Continuous collector current	T_{case} = 70˚C	600	A
$I_{C(PK)}$	Peak collector current	1ms, T_{case} = 105˚C	1200	A
P_{max}	Max. transistor power dissipation	T_{case} = 25˚C, T_j = 150˚C	4630	W
I^2t	Diode I^2t value (IGBT arm)	V_R = 0, t_p = 10ms, T_{vj} = 125˚C	120	kA^2s
	Diode I^2t value (Diode arm)		120	kA^2s
V_{isol}	Isolation voltage - per module	Commoned terminals to base plate. AC RMS, 1 min, 50Hz	4000	V
Q_{PD}	Partial discharge - per module	IEC1287. V_1 = 1500V, V_2 = 1100V, 50Hz RMS	10	pC

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

THERMAL AND MECHANICAL RATINGS

Internal insulation material: AlN
Baseplate material: AlSiC
Creepage distance: 20mm
Clearance: 10mm
CTI (Critical Tracking Index): 175

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$R_{th(j-c)}$	Thermal resistance - transistor (per arm)	Continuous dissipation - junction to case	-	-	27	˚C/kW
$R_{th(j-c)}$	Thermal resistance - diode (IGBT arm)	Continuous dissipation - junction to case	-	-	40	˚C/kW
	Thermal resistance - diode (Diode arm)		-	-	40	˚C/kW
$R_{th(c-h)}$	Thermal resistance - case to heatsink (per module)	Mounting torque 5Nm (with mounting grease)	-	-	8	˚C/kW
T_j	Junction temperature	Transistor	-	-	150	˚C
		Diode	-	-	125	˚C
T_{stg}	Storage temperature range	-	–40	-	125	˚C
-	Screw torque	Mounting - M6	-	-	5	Nm
		Electrical connections - M4	-	-	2	Nm
		Electrical connections - M8	-	-	10	Nm

ELECTRICAL CHARACTERISTICS

T_{case} = 25˚C unless stated otherwise.

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Units
I_{CES}	Collector cut-off current	V_{GE} = 0V, V_{CE} = V_{CES}		-	-	1	mA
		V_{GE} = 0V, V_{CE} = V_{CES}, T_{case} = 125˚C		-	-	20	mA
I_{GES}	Gate leakage current	V_{GE} = ±20V, V_{CE} = 0V		-	-	4	µA
$V_{GE(TH)}$	Gate threshold voltage	I_C = 30mA, V_{GE} = V_{CE}		4.5	5.5	6.5	V
$V_{CE(sat)}$ †	Collector-emitter saturation voltage	V_{GE} = 15V, I_C = 600A		-	2.7	3.2	V
		V_{GE} = 15V, I_C = 600A, , T_{case} = 125˚C		-	3.4	4.0	V
I_F	Diode forward current	DC		-	-	600	A
I_{FM}	Diode maximum forward current	t_p = 1ms		-	-	1200	A
V_F †	Diode forward voltage (IGBT arm)	I_F = 600A		-	2.0	2.3	V
	Diode forward voltage (Diode arm)			-	2.0	2.3	V
	Diode forward voltage (IGBT arm)	I_F = 600A, T_{case} = 125˚C		-	2.1	2.4	V
	Diode forward voltage (Diode arm)			-	2.1	2.4	V
C_{ies}	Input capacitance	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz		-	45	-	nF
C_{res}	Reverse transfer capacitance	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz		-	3.8	-	nF
L_M	Module inductance - per arm	-		-	20	-	nH
R_{INT}	Internal transistor resistance - per arm	-		-	0.27	-	mΩ
SC_{Data}	Short circuit. I_{SC}	T_j = 125˚C, V_{CC} = 1000V,	I_1		2780	-	A
		t_p ≤ 10µs, $V_{CE(max)}$ = V_{CES} – L*. di/dt	I_2		2400	-	A
		IEC 60747-9					

Note:
† Measured at the power busbars and not the auxiliary terminals)
* L is the circuit inductance + L_M

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

ELECTRICAL CHARACTERISTICS

T_{case} = 25°C unless stated otherwise

Symbol	Parameter		Test Conditions	Min.	Typ.	Max.	Units
$t_{d(off)}$	Turn-off delay time		I_C = 600A	-	1200	-	ns
t_f	Fall time		V_{GE} = ±15V	-	140	-	ns
E_{OFF}	Turn-off energy loss		V_{CE} = 900V	-	190	-	mJ
$t_{d(on)}$	Turn-on delay time		$R_{G(ON)}$ = $R_{G(OFF)}$ = 3.3Ω	-	250	-	ns
t_r	Rise time		L ~ 100nH	-	250	-	ns
E_{ON}	Turn-on energy loss			-	220	-	mJ
Q_g	Gate charge			-	6.8	-	µC
Q_{rr}	Diode reverse recovery charge	Diode arm	I_F = 600A,	-	370	-	µC
		IGBT arm	V_R = 50% V_{CES},	-	150	-	µC
I_{rr}	Diode reverse recovery current	Diode arm	dI_F/dt = 3000A/µs	-	800	-	A
		IGBT arm		-	350	-	A
E_{rec}	Diode reverse recovery energy	Diode arm		-	250	-	mJ
		IGBT arm		-	100	-	mJ

ELECTRICAL CHARACTERISTICS

T_{case} = 125˚C unless stated otherwise

Symbol	Parameter		Test Conditions	Min.	Typ.	Max.	Units
$t_{d(off)}$	Turn-off delay time		I_C = 600A	-	1500	-	ns
t_f	Fall time		V_{GE} = ±15V	-	170	-	ns
E_{OFF}	Turn-off energy loss		V_{CE} = 900V	-	270	-	mJ
$t_{d(on)}$	Turn-on delay time		$R_{G(ON)}$ = $R_{G(OFF)}$ = 3.3Ω	-	400	-	ns
t_r	Rise time		L ~ 100nH	-	250	-	ns
E_{ON}	Turn-on energy loss			-	350	-	mJ
Q_{rr}	Diode reverse recovery charge	Diode arm	I_F = 600A,	-	650	-	µC
		IGBT arm	V_R = 50% V_{CES},	-	250	-	µC
I_{rr}	Diode reverse recovery current	Diode arm	dI_F/dt = 3000A/µs	-	900	-	A
		IGBT arm		-	400	-	A
E_{rec}	Diode reverse recovery energy	Diode arm		-	380	-	mJ
		IGBT arm		-	150	-	mJ

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

www.dynexsemi.com

TYPICAL CHARACTERISTICS



Fig. 3 Typical output characteristics



Fig. 4 Typical output characteristics



Fig. 5 Typical switching energy vs collector current



Fig. 6 Diode typical forward characteristics



Fig. 7 Reverse bias safe operating area



Fig. 8 Diode reverse bias safe operating area



Fig. 9 Forward bias safe operating area



		1	2	3	4
IGBT	R_i (˚C/KW)	0.65865	5.7785	6.2197	15.3534
	τ_i (ms)	0.045	2.8869	21.7141	152.6381
Freewheel and Antiparallel Diode	R_i (˚C/KW)	1.5612	5.7426	6.999	25.6068
	τ_i (ms)	0.0063516	1.4746	13.9664	111.7517

Fig. 10 Transient thermal impedance

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.



Fig. 11 DC current rating vs case temperature

PACKAGE DETAILS

For further package information, please visit our website or contact Customer Services. All dimensions in mm, unless stated otherwise. DO NOT SCALE.



Nominal weight: 1050g

Module outine type code: D

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.

POWER ASSEMBLY CAPABILITY

The Power Assembly group was set up to provide a support service for those customers requiring more than the basic semiconductor, and has developed a flexible range of heatsink and clamping systems in line with advances in device voltages and current capability of our semiconductors.

We offer an extensive range of air and liquid cooled assemblies covering the full range of circuit designs in general use today. The Assembly group continues to offer high quality engineering support dedicated to designing new units to satisfy the growing needs of our customers.

Using the latest CAD methods our team of design and applications engineers aim to provide the Power Assembly Complete Solution (PACs).

HEATSINKS

The Power Assembly group has its own proprietary range of extruded aluminium heatsinks. They have been designed to optimise the performance of Dynex semiconductors. Data with respect to air natural, forced air and liquid cooling (with flow rates) is available on request.

For further information on device clamps, heatsinks and assemblies, please contact your nearest sales representative or customer service office.

http://www.dynexsemi.com

e-mail: power_solutions@dynexsemi.com

HEADQUARTERS OPERATIONS
DYNEX SEMICONDUCTOR LTD
Doddington Road, Lincoln.
Lincolnshire. LN6 3LF. United Kingdom.
Tel: 00-44-(0)1522-500500
Fax: 00-44-(0)1522-500550

CUSTOMER SERVICE
Tel: +44 (0)1522 502753 / 502901. Fax: +44 (0)1522 500020

SALES OFFICES
Benelux, Italy & Switzerland: Tel: +33 (0)1 64 66 42 17. Fax: +33 (0)1 64 66 42 19.
France & Spain: Tel: +33 (0)2 47 55 75 52. Fax: +33 (0)2 47 55 75 59.
Germany, Northern Europe & Rest Of World: Tel: +44 (0)1522 502753 / 502901. Fax: +44 (0)1522 500020
North America: Tel: (613) 723-7035. Fax: (613) 723-1518. Toll Free: 1.888.33.DYNEX (39639) /
Tel: (949) 733-3005. Fax: (949) 733-2986.

These offices are supported by Representatives and Distributors in many countries world-wide.
© Dynex Semiconductor 2002 Publication No. DS5491-2 Issue No. 2.0 March 2002
TECHNICAL DOCUMENTATION – NOT FOR RESALE. PRODUCED IN UNITED KINGDOM

Datasheet Annotations:

Dynex Semiconductor annotate datasheets in the top right hard corner of the front page, to indicate product status. The annotations are as follows:-

Target Information: This is the most tentative form of information and represents a very preliminary specification. No actual design work on the product has been started.

Preliminary Information: The product is in design and development. The datasheet represents the product as it is understood but details may change.

Advance Information: The product design is complete and final characterisation for volume production is well in hand.

No Annotation: The product parameters are fixed and the product is available to datasheet specification.

This publication is issued to provide information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose nor form part of any order or contract nor to be regarded as a representation relating to the products or services concerned. No warranty or guarantee express or implied is made regarding the capability, performance or suitability of any product or service. The Company reserves the right to alter without prior notice the specification, design or price of any product or service. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date and has not been superseded. These products are not suitable for use in any medical products whose failure to perform may result in significant injury or death to the user. All products and materials are sold and services provided subject to the Company's conditions of sale, which are available on request.

All brand names and product names used in this publication are trademarks, registered trademarks or trade names of their respective owners.

Caution: This device is sensitive to electrostatic discharge. Users should follow ESD handling procedures.